## Garmin ECHOMAP UHD 72sv, 73sv, 74sv & 75sv Specifications

BURGO AL BURGO AND	0.011
PHYSICAL DIMENSIONS	9.8" x 5.5" x 2.0" (25 x 13.9 x 5.1 cm)
DISPLAY SIZE	6.1" x 3.4"; 7.0" diagonal (15.5 x 8.6 cm; 17.8 cm diagonal
DISPLAY RESOLUTION	400 x 800 pixels
DISPLAY TYPE	WVGA display
WEIGHT	1.7 lbs.(0.77kg)
WATER RATING	IPX7
POWER CONSUMPTION	15W
ANTENNA	Internal or external over NMEA 2000
MOUNTING OPTIONS	Bail or flush
RECEIVER	5 Hz
GARMIN MARINE NETWORK™ PORTS	1 Panoptix™ port
TRANSMIT POWER	500 W (RMS) / 4,000 W (peak to peak)
Maps & Memory	
PRELOADED MAPS	72sv: Worldwide basemap
	73sv: U.S. BlueChart g3 (coastal maps)
	74sv: U.S. LakeVü g3 (inland maps)
	75sv: Canada LakeVü g3 (inland maps)
ACCEPTS DATA CARDS	1 microSD™ card; 32 GB maximum card size
WAYPOINTS	5,000
TRACK LOG	50,000 points; 50 saved tracks
ROUTES	100
Outdoor Recreation	
TIDE TABLES	✓
Chartplotter Features	
GARMIN SONAR COMPATIBLE	✓
SUPPORTS AIS (TRACKS TARGET SHIPS POSITION)	✓
SUPPORTS DSC (DISPLAYS POSITION DATA FROM DSC-CAPABLE VHF RADIO)	✓
GCV™ BLACK BOX SONAR SUPPORT	✓
ACTIVECAPTAIN COMPATIBLE	✓
SAILING FEATURES	✓
Sonar Features & Specifications	
DUAL-FREQUENCY (50/200 KHZ) SONAR CAPABLE	✓
DUAL-BEAM (77/200 KHZ) SONAR CAPABLE	✓
CHIRP SONAR TECHNOLOGY	Yes (Built-in)
CLEARVÜ	Yes with CHIRP (built-in)
SIDEVÜ	Yes with CHIRP (built-in)

MAXIMUM DEPTH	2,300 ft @ 77 kHz, freshwater
	1,100 ft @ 77 kHz, saltwater
	(depth capacity is dependent on water bottom type and
	other water conditions)
BOTTOM LOCK (SHOWS RETURN FROM THE	✓
BOTTOM UP)	
WATER TEMPERATURE LOG AND GRAPH	✓
SONAR RECORDING	✓
SONAR HISTORY REWIND	✓
Connections	
NMEA 2000® COMPATIBLE	✓
TRANSDUCER PIN NUMBERS	12
NMEA 0183 INPUT PORTS	1
NMEA 0183 OUTPUT PORTS	1
VIDEO INPUT PORTS	None
VIDEO OUTPUT PORTS	None
WIRELESS CONNECTIVITY	✓