Product Specifications GPSMAP® 8424 MFD

General			
PHYSICAL DIMENSIONS	22.8" x 16.1" x 2.8" (60.0 cm x 41.0 cm x 7.1 cm)		
DISPLAY SIZE	20.4" x 12.8"; 24.0" diagonal (51.8 x 32.5 cm; 61.0 cm diagonal)		
DISPLAY RESOLUTION	1920 x 1200 pixels		
DISPLAY TYPE	Touchscreen IPS display (anti-glare finish)		
WEIGHT	18.95 lbs (8.60 kg)		
WATER RATING	IPX7		
MOUNTING OPTIONS	Flush or Flat		
POWER CONSUMPTION	Max power usage at 10 Vdc: 87 W Typical current draw at 12 Vdc: 6.1 A Max current draw at 12 Vdc: 7.6 A		
ANTENNA	External only		
RECEIVER	10 Hz high-sensitivity		
GARMIN MARINE NETWORK™ PORTS	4		

Maps & Memory

PRELOADED MAPS	None
ACCEPTS DATA CARDS	2 SD Cards (with Garmin SD card reader accesory)
WAYPOINTS	5,000
TRACK LOG	50,000 points; 50 saved tracks, with 5000 points each
ROUTES	100 (250 waypoints each)

Outdoor Recreation

TIDE TABLES	Yes
Chartplotter Features	
GARMIN RADAR COMPATIBLE	Yes
GARMIN SONAR COMPATIBLE	Yes
GARMIN SMARTMODE COMPATIBLE (CUSTOMIZABLE MONITOR PRESETS)	Yes
SUPPORTS AIS (TRACKS TARGET SHIPS POSITION)	Yes
SUPPORTS DSC (DISPLAYS POSITION DATA FROM DSC-CAPABLE VHF RADIO)	Yes
GARMIN METEOR™ AUDIO SYSTEM COMPATIBLE	Yes

SUPPORTS FUSION-LINK™ COMPATIBLE RADIOS			Yes		
GSD™ BLACK BOX SONAR SUPPORT			Yes		
GCV™ BLACK BOX SONAR SUPPORT			Yes		
ACTIVECAPTAIN COMPATIBLE				Yes	
GRID™ (GARMIN REMOTE INPUT DEVICE) COMPATIBLE				Yes	
Sonar Featu	res & Specifications				
DUAL-FREQUENCY (50/200 KHZ) SONAR CAPABLE		Yes (with external black box, sold separately)			
DUAL-BEAM (77/200 KHZ) SONAR CAPABLE			Yes (with external black box, sold separately)		
CHIRP SONAR TECHNOLOGY			Yes (with external black box, sold separately)		
CLEARVÜ			Yes (with GCV™ black box, sold separately)		
SIDEVÜ			Yes (with GCV™ black box, sold separately)		
Connection	S				
NMEA 2000® COMPATIBLE		Y	es		
NMEA 0183 INPUT PORTS		4			
NMEA 0183 OUTPUT PORTS		2			
VIDEO INPUT PORTS		1 - BNC composite 1 - HDMI (HDCP compliant)			
VIDEO OUTPUT PORTS		1 - HDMI			
WIRELESS CONNECTIVITY		Yes			
Additional		1			
ADDITIONAL	Additional connections: • NMEA 2000 port: 1 • USB port: 1 • J1939 port: 1 HDMI and composite video inputs are e to other comaptible chartplotters.	encod	ed and shared across the Garmin Marine N	etwork	